# ADVANCE CARE #P

# Head Activated Call Device

The Advance Care range of specialised Call Devices have been designed for those with limited movement in mind.

The Head Activated Call Device is a sensitive touch pad which can be utilised in a variety of environments and a number of different applications.

This device can be positioned to be activated by the foot, hand, elbow or head, thus ensuring ease of usage for residents with many different movement limitations.

The Head Activated Call Device comes with two secure clips and a Velcro strap, allowing for the easy attachment to a resident's pillow or clothing or to be seamlessly mounted onto a bed rail, ensuring it stays within the resident's reach.

As the Head Activated Call Device is plugged into the Nurse Call Button via the tough, fully moulded 6.35mm jack into the pendant socket on the front of the plate, the Call Pendant essentially acts as an extension of the Nurse Call Button, allowing for the easy access of a Call Point without having to strain reaching the wall.

Although an extension of the Nurse Call Button, when activated, the Call Device has its own easily identifiable alert, such as 'Head Device Call Room 1'. When a call is made, a high visibility reassurance light illuminates the 'CANCEL' button on the Call Button plate and the Call Button may also 'beep' periodically (if activated), providing reassurance to the user.

The Nurse Call alert is immediately displayed at the Nurse Station and sent to associated paging devices.

The Advance Care IP Nurse Call System includes a 'Pendant Removed' alarm feature which generates an alert if the pendant is accidently pulled out or incorrectly plugged in, a beneficial feature with resident safety as key.

This product integrates with most Nurse Call Systems and is a valued addition to any Advance Care IP Nurse Call installation.

### **Features**

- · Low pressure, sturdy pad
- · Minimum push pressure required
- Purposely designed for those with restricted movement
- Durable fully moulded fittings
- Integrates with most Nurse Call Systems
- 6.35mm industry standard Pendant Plug
  - Self-configured alarm notification
    - · Bed clip as standard
    - Ergonomic design

Low Pressure, Sturdy Pad









# **Tender Specifications**

Supply and install assistive Call Devices where indicated on the drawings.

The device will be ergonomically designed for ease of use by residents with limited dexterity to activate calls.

The device will be activated by a simple low-pressure press by the user with any active part of their body.

The Call Device shall have an impact resistant case and be tamper proof against disassembly by residents, children, staff and intentional or unintentional impact.

The Call Device will be fitted with an injection moulded right angle 6.35mm phono plug.

The Call Device is to act as an extension of the Nurse Call Button, allowing for the easy access of a Call Point without having to physically touch the wall. The Call Device is to have its own easily identifiable alert, such as 'Call Device Call Room 1'.

When a call is made, a high visibility reassurance light is to illuminates the 'CANCEL' button on the connected Call Button plate and the Call Button may also 'beep' periodically (if activated), to provide reassurance to the user.

Removal of the Call Device, either intentionally or by accident, will result in a call being activated common to that of the original call. The pendant removal alarm can only be reset by reinserting a Pendant Plug or by inserting Dummy Plug.

The Call Device is to be securely clamped to any adjacent fitting, such as a bed rail, allowing the device to be positioned in the most appropriate location to best suit the resident's needs.

## **Design Specifications**

Feature	Description
Height	110mm
Width	127mm
Depth	110mm
Weight	210 grams
Material	Silicone
Connectors	6.35mm Phono Plug
Temperature	-20°C to 50°C
Humidity Range	0 to 90%

# Compliance

Designed to comply with:

- AS/NZS 3811 Hard Wired Patient Alarm Systems
- · AS/NZS 2999 Alarm Systems for the Elderly and Other Persons at Risk
- · AS/NZS 3000 Wiring Rules
- AS/NZS CISPR22 (Class B) Electromagnetic Compatibility (EMC)

© 2015 Digital Telecommunication Systems (WA) Pty Ltd

All rights are reserved.

Digital Telecommunication Systems (WA) Pty Ltd reserves the right to make changes in specifications and/or discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

**Authorised Distributor** 

